

Raffia Weave

Item # P3T-60045 - P3T-60059 (15 colorways)

 Impact  Chemical  Abrasion

PHYSICAL PROPERTIES		 Impact	 Chemical	 Abrasion
Width	Trim to 48"	Impact Resistance	Chemical Resistance	Cleaning
Packaging	15-yd rolls	ASTM D- 5420-10	ASTM D-1308	ASTM F-793
Thickness	0.035	Gardner Method	Spot test covered 3.1.1	SECTION 7.5
Backing	Heavy Polyester/ Cotton knit			
Repeat	N/A	Pattern	Cleaning Agents	Staining Agents
Installation	Reverse hang, Random match	In-Lbs	Tide w/H2O	Test Spec
Fire Safety	Class "A" rated ASTM E-84	Raffia Weave 60	Virex	CS-10F wheel
			Ammonia	500 gram load @200 cycles
			Isopropyl Alcohol	Weight loss: 0.02%
			Goof Off	
			Fantastik	
			Lysol	
			Hydrogen Peroxide	
			Bleach	
			Methyl Ethyl Ketone	
			Results: No change in P3TEC surface from exposure to these agents.	Results: Each staining agent above was wiped clean with at least one listed cleaning agent.
			Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.	

OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)