

Balance

Item # P3T-60270 - P3T-60289 (17 colorways)

 Impact  Chemical  Abrasion

PHYSICAL PROPERTIES		 Impact	 Chemical	 Abrasion
Width	Trim to 48"	Impact Resistance	Chemical Resistance	Cleaning
Packaging	15-yd rolls	ASTM D- 5420-10	ASTM D- D-1308	ASTM F-793
Thickness	0.030	Gardner Method	Spot test covered 3.1.1	SECTION 7.5
Backing	Heavy Polyester/ Cotton knit			
Repeat	N/A	Pattern	Cleaning Agents	Staining Agents
Installation	Reverse hang, Random match	In-Lbs	Tide w/H2O	Grape Juice
Fire Safety	Class "A" rated ASTM E-84	Balance	Virex	Mustard
			Ammonia	Black Sharpie
			Isopropyl Alcohol	Ink Pen
			Goof Off	Betadine
			Fantastik	Shoe Polish
			Lysol	Lipstick
			Hydrogen Peroxide	Black Rubber
			Bleach	Brake Fluid
			Methyl Ethyl Ketone	Spray Paint
			Results: No change in P3TEC surface from exposure to these agents.	Results: Each staining agent above was wiped clean with at least one listed cleaning agent.
			Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.	
ENVIRONMENTAL & HEALTH				
Indoor Air	Meets California Section 01350			
Fungal Resistant	ASTM G-21			
Bacterial Resistant	ASTM G-22			
HPD	third-party certified			
EPD	third-party certified			
NSF/ANSI 342	third-party certified, ask distributor for details			
Recycled content				
California Prop 65, no labeling required				
Non-phthalate				

OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similiar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full installation instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)