

# In-Grained

Item # P3T-60155 - P3T-60165 (11 colorways)

 Impact

 Chemical

 Abrasion

## PHYSICAL PROPERTIES

|              |                                     |
|--------------|-------------------------------------|
| Width        | Trim to 48"                         |
| Packaging    | 15-yd rolls                         |
| Thickness    | 0.037                               |
| Backing      | Heavy Polyester/ Cotton knit        |
| Repeat       | N/A                                 |
| Installation | Reverse hang, Random match          |
| Fire Safety  | Class "A" rated ASTM E-84; NFPA 286 |

### Impact

Impact Resistance  
ASTM D- 5420-10  
Gardner Method

|            |        |
|------------|--------|
| Pattern    | In-Lbs |
| In-Grained | 60     |

### Chemical

Chemical Resistance  
ASTM D- 1308  
Spot test covered 3.1.1

Cleaning Agents  
Tide w/H2O  
Virex  
Ammonia  
Isopropyl Alcohol  
Goof Off  
Fantastik  
Lysol  
Hydrogen Peroxide  
Bleach  
Methyl Ethyl Ketone

Results: No change in P3TEC surface from exposure to these agents.

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

Cleaning  
ASTM F-793  
SECTION 7.5

Staining Agents  
Grape Juice  
Mustard  
Black Sharpie  
Ink Pen  
Betadine  
Shoe Polish  
Lipstick  
Black Rubber  
Brake Fluid  
Spray Paint

Results: Each staining agent above was wiped clean with at least one listed cleaning agent.

### Abrasion

Abrasion Resistance  
ASTM D- 4060-14  
Taber Method

Test Spec  
CS-10F wheel  
500 gram load @200 cycles  
Weight loss: 0.02%

## ENVIRONMENTAL & HEALTH

|                     |                                |
|---------------------|--------------------------------|
| Indoor Air          | Meets California Section 01350 |
| Fungal Resistant    | ASTM G-21                      |
| Bacterial Resistant | ASTM G-22                      |
| HPD                 | third- party classified        |
| EPD                 | third- party certified         |

## OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.  
See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)